T2 P FP 4p F 1/3



PRODUCT-DETAILS

T2 P FP 4p F T2 P FP 4p F



General Information	
Extended Product Type	T2 P FP 4p F
Product ID	1SDA051330R1
EAN	8015644517519
Catalog Description	T2 P FP 4p F
Long Description	FIXED PART PLUG-IN FOR C.BREAKER TMAX FOUR-POLE WITH FRONT TERMINALS T2

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	Document availability on demand
Toxic Substances Control Act - TSCA	9AKK108467A8326

T2 P FP 4p F 2/3

Ordering	
Order Code US and	KT2PFF-4
Canada	
EAN	8015644517519
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions	
Product Net Width	90 mm
Product Net Height	170 mm
Product Net Depth / Length	70 mm
Product Net Weight	0.993 kg

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	115 mm
Package Level 1 Height	149 mm
Package Level 1 Depth / Length	185 mm
Package Level 1 Gross Weight	1.065 kg
Package Level 1 EAN	8015644517519

Additional Information	
Product Main Type	Accessories for Tmax T
Product Name	Fixed Part
Product Type	Fixed Part
Suitable For	T2
Suitable for Product	Moulded Case Circuit Breakers
Class	
Version	Р

Device	Fixed Part
Number of Poles	4P
Rated Operational	690 V AC
Voltage	500 V DC
Standards	IEC
Sub-type Sub-type	T2
Terminal Connection	Plug-In Circuit-Breakers
Туре	Front
Test Voltage at Industrial	not applicable V
Frequency for 1 Minute	

Certificates and Declarations	
Data Sheet, Technical	1SDC210004D0202
Information	

T2 P FP 4p F 3/3

Declaration of Conformity - CE	Refer to the EU Declaration of the relative Circuit Breaker
Instructions and Manuals	ITSCE-RH0012001
Instructions and Manuals (Part 2)	ITSCE-RH0100.001
Instructions and Manuals (Part 3)	ITSCE-RH0012002

External Classifications and Standards	
Object Classification Code	Q
UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Circuit\ Breakers \rightarrow Moulded\ Case\ Circuit\ Breakers \rightarrow Tmax\ T$

