



PRODUCT-DETAILS

QSD-DIG 230/24

Remote signalling panel



General Information	
Extended Product Type	QSD-DIG 230/24
Product ID	2CSM273063R1521
EAN	8012542730637
Catalog Description	Remote signalling panel
Long Description	Remote signalling panel for visual and acoustic fault indication.

Technical	
Model Number	Basic device
Delay Time (T)	Release 0...0 second [unit of time]

Electrical	
Rated Operational Voltage	500 ... 760 V AC
Rated Control Supply Voltage (U _S)	24 V DC
At Rated Load 1 W	

Material Compliance	
RoHS Information	9AKK106713A5709
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20180713
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Environmental	
Environmental Information	See RoHS Information

Dimensions	
Product Net Width	121 mm
Product Net Height	78 mm
Product Net Depth / Length	55 mm
Product Net Weight	200 g

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.5 kg
Replacement Product ID (NEW)	2CSM257935R1521

Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A5709

Installation	
Instructions and Manuals	9AKK107046A3897
Mounting Orientation	Horizontal

Popular Downloads	
Data Sheet, Technical Information	2CSC004033B0202

External Classifications and Standards	
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
eClass	V11.0 : 27371819

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Hospital Equipments (H+ Line) → Insulation Monitoring Devices for Medical Locations, ISOLTESTER - SELVTESTER - QSD

