



PRODUCT-DETAILS

ISL-C 230

Insulation monitor



General Information

Extended Product Type	ISL-C 230
Product ID	2CSM444000R1500
EAN	8012542942801
Catalog Description	Insulation monitor
Long Description	ISL-C 230 is an insulation monitoring device for ac circuits

Technical

Model Number	Basic device
Delay Time (T)	Release 0...1 second [unit of time]
Options Provided	AC network

Electrical

Rated Operational Voltage	220 ... 240 V AC
Rated Control Supply Voltage (U _s)	(50 Hz) 230...230 V (60 Hz) 230...230 V
Power Loss	at Rated Operating Conditions per Pole 4 W

Material Compliance		
RoHS Information		9AKK108467A8682
RoHS Status	Following EU Directive 2011/65/EU	
RoHS Date		20231022
Conflict Minerals Reporting Template (CMRT)		9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B		Business To Consumer

Environmental		
Environmental Information		See RoHS Information

Dimensions		
Product Net Width		85 mm
Product Net Height		85 mm
Product Net Depth / Length		58 mm
Product Net Weight		90 g

Ordering		
Package Level 1 Units		box 1 piece
Package Level 1 Gross Weight		0.3 kg

Certificates and Declarations		
Declaration of Conformity - CE		9AKK108467A8682

Installation		
Instructions and Manuals		9AKK108469A0619 9AKK108469A0986

Popular Downloads		
Data Sheet, Technical Information		9AKK108469A0611

External Classifications and Standards		
ETIM 9	EC001449 - Device for monitoring of safety-related circuits	
eClass		V11.0 : 27371819
Object Classification Code		F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Industrial Insulation Monitoring Devices

