



PRODUCT-DETAILS

UPS PowerValue 11T G2 3 kVA B

UPS PowerValue 11T G2 3 kVA B



General Information

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Extended Product Type | UPS PowerValue 11T G2 3 kVA B                                   |
| Product ID            | 4NWP100162R0001                                                 |
| EAN                   | 7640169261923                                                   |
| Catalog Description   | UPS PowerValue 11T G2 3 kVA B                                   |
| Long Description      | VFI online double conversion:2700W:9min:RS232:USB:mini COM slot |

Environmental

|                           |                       |
|---------------------------|-----------------------|
| Environmental Information | No declaration needed |
|---------------------------|-----------------------|

Material Compliance

|                                             |                                   |
|---------------------------------------------|-----------------------------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                   |
| REACH Declaration                           | 4NWD004620                        |
| RoHS Information                            | 4NWD004828                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU |

|                                  |                                                                                |
|----------------------------------|--------------------------------------------------------------------------------|
| Technical                        |                                                                                |
| Input Voltage (U <sub>in</sub> ) | 220 V<br>230 V<br>240 V                                                        |
| Input Voltage Type               | AC                                                                             |
| Rated Frequency (f)              | Primary 50 Hz<br>Primary 60 Hz<br>Secondary 50 Hz<br>Secondary 60 Hz           |
| Apparent Power Output            | 3000 V·A                                                                       |
| Rated Output Power               | 2700 W                                                                         |
| Communication Interface          | USB, RS-232                                                                    |
| Number of Phases                 | Primary - 1<br>Secondary - 1                                                   |
| Number of Outputs                | C13 Connection 4<br>C19 Connection 1                                           |
| Connection Type                  | IEC C20                                                                        |
| Options Provided                 | Auto shut down function<br>Potential free switch contact<br>Network-management |
| Battery Chemical Composition     | Lead-Acid                                                                      |
| Battery Type                     | Portable                                                                       |
| Battery Weight                   | 2.5 kg                                                                         |
| Number of Batteries              | 4                                                                              |

|                            |         |
|----------------------------|---------|
| Dimensions                 |         |
| Product Net Width          | 190 mm  |
| Product Net Height         | 327 mm  |
| Product Net Depth / Length | 399 mm  |
| Product Net Weight         | 22.2 kg |

|                                |               |
|--------------------------------|---------------|
| Container Information          |               |
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 324 mm        |
| Package Level 1 Height         | 464 mm        |
| Package Level 1 Depth / Length | 500 mm        |
| Package Level 1 Gross Weight   | 24.6 kg       |
| Package Level 1 EAN            | 7640169261923 |

|                        |            |
|------------------------|------------|
| Ordering               |            |
| Minimum Order Quantity | 1 piece    |
| Customs Tariff Number  | 85044000   |
| E-Number (Finland)     | 8408612    |
| E-Number (Sweden)      | 5257249    |
| Country of Origin      | China (CN) |

|                                 |                         |
|---------------------------------|-------------------------|
| Certificates and Declarations   |                         |
| Declaration of Conformity - CCC | No certification needed |
| Declaration of Conformity       | 4NWD004828              |

- CE

Popular Downloads

|                                   |               |
|-----------------------------------|---------------|
| Data Sheet, Technical Information | 4NWD003883_EN |
| Instructions and Manuals          | 4NWD003883_EN |

Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| ETIM 7                     | EC000382 - UPS                                             |
| ETIM 8                     | EC000382 - UPS                                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B             | Business To Business                                       |
| CN8                        | 85044000                                                   |
| eClass                     | V11.1 : 27040690                                           |
| Object Classification Code | G                                                          |

Categories

UPS, Power Conditioning and Power Distribution → UPS → Single-Phase UPS → PowerValue 11 T G2 IEC 230V

