



6AG1226-6DA32-5XB0



SIPLUS S7-1200 SM 1226 F-DQ 4x24VDC based on 6ES7226-6DA32-0XB0 with conformal coating, -25...+55 °C, F-DQ 4x DC 24V 2A, PROFIsafe, 70 mm width, up to PL e (ISO 13849-1)/ SIL3 (IEC 61508)	
List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6AG1226-6DA32-5XB0
Product Description	SIPLUS S7-1200 SM 1226 F-DQ 4x24VDC based on 6ES7226-6DA32-0XB0 with conformal coating, -25...+55 °C, F-DQ 4x DC 24V 2A, PROFIsafe, 70 mm width, up to PL e (ISO 13849-1)/ SIL3 (IEC 61508)
Product family	SIPLUS SM 1226 fail-safe digital output
Product Lifecycle (PLM)	PM300:Active Product

Price data

Price Group	472
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : 9N9999
Estimated dispatch time (Working Days)	55 Day/Days
Net Weight (kg)	0,270 Kg
Packaging Dimension	8,50 x 10,70 x 9,00
Package size unit of measure	CM
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	4047618064723
UPC	804766353369
Commodity Code	85389091
LKZ_FDB/ CatalogID	A&DSE/SIP ADD
Product Group	4578
Group Code	R151
Country of origin	Germany
Compliance with the substance restrictions according to RoHS directive	Since: 27.11.2014
Product class	B: return restricted, please contact your Siemens partner/contact
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	1200	27-24-22-04
eClass	1400	27-24-22-04
eClass	600	27-24-22-04
eClass	710	27-24-22-04
eClass	800	27-24-22-04
eClass	900	27-24-22-04
eClass	910	27-24-22-04
ETIM	700	EC001419
ETIM	800	EC001419
ETIM	900	EC001419
IDEA	400	3566
UNSPSC	1500	32-15-17-05