

6AG2620-0AA00-4AA0



SIPLUS PN/CAN link TX rail based on 6BK1620-0AA00-0AA0 with conformal coating, -40...+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), module PROFINET to CAN or CANopen Fieldbus CAN 2.0 A/B CANopen Manager or Slave according to CiA301/302 IP20

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6AG2620-0AA00-4AA0
Product Description	SIPLUS PN/CAN link TX rail based on 6BK1620-0AA00-0AA0 with conformal coating, -40...+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), module PROFINET to CAN or CANopen Fieldbus CAN 2.0 A/B CANopen Manager or Slave according to CiA301/302 IP20
Product family	SIPLUS PN/CAN LINK TX RAIL
Product Lifecycle (PLM)	PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group	471 / 471
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : 9N9999
Estimated dispatch time (Working Days)	55 Day/Days
Net Weight (kg)	0,276 Kg
Packaging Dimension	8,00 x 12,00 x 9,00
Package size unit of measure	CM
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	4047618085704
UPC	804766730030
Commodity Code	85176200
LKZ_FDB/ CatalogID	A&DSE/SIP ADD
Product Group	4C01
Group Code	R151
Country of origin	Germany
Compliance with the substance restrictions according to RoHS directive	Since: 13.12.2017
Product class	B: return restricted, please contact your Siemens partner/contact
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	1200	27-24-22-08
eClass	1400	27-24-22-08
eClass	600	27-24-22-08
eClass	710	27-24-22-08
eClass	800	27-24-22-08
eClass	900	27-24-22-08
eClass	910	27-24-22-08
ETIM	700	EC001423
ETIM	800	EC001423
ETIM	900	EC001423
IDEA	400	3564
UNSPSC	1500	32-15-17-05