

6AG4114-3MD28-5HJ0

SIMATIC IPC847E (Rack PC, 19", 4HU); 3x Gbit Ethernet (IE/PN), RJ45; 1x DVI-D; 2x display ports; 1x COM 1; audio, 4x USB 3.1, 2x USB 3.1 (Type C) on the rear side; 2x USB 3.0 on the front; 1x USB 3.1 internal, temperature and fan monitoring; Watchdog, card retainer Xeon E-2176G (6C/12T, 3.7 (4.7) GHz, 12 MB cache, TB, VT-D, AMT); Board 11 slots: 3x PCI, 1x PCIe x16 (16 L), 3x PCIe x16 (4 L), 2x PCIe x16 (1 L); 2x PCIe x4 (4 L); RAID1, 2x 2 TB HDD (Enterprise) 3.5" SATA; Enclosure with drive support Type B (for internal installation/ 0.5 g vibration, 5 g shock); 2x 100/240V AC redundant industrial power supply unit; 64 GB DDR4 SDRAM (4x 16 GB), ECC, Dual Channel (only with Xeon); 512 GB SSD M.2 NVMe to PCIe x4 adapter card (1 slot occupied); (for operating system) and PCIe x16 graphics card (3x mDP: 3x adapter mDP to DP) (1 slot occupied); Windows Server 2016 Standard edition including clients, 64-bit, MUL (de, en, fr, it, es); Adapter cable DP acc. to DVI-D for onboard graphic; Without power supply cable

Image similar

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6AG4114-3MD28-5HJ0
Product Description	SIMATIC IPC847E (Rack PC, 19", 4HU); 3x Gbit Ethernet (IE/PN), RJ45; 1x DVI-D; 2x display ports; 1x COM 1; audio, 4x USB 3.1, 2x USB 3.1 (Type C) on the rear side; 2x USB 3.0 on the front; 1x USB 3.1 internal, temperature and fan monitoring; Watchdog, card retainer Xeon E-2176G (6C/12T, 3.7 (4.7) GHz, 12 MB cache, TB, VT-D, AMT); Board 11 slots: 3x PCI, 1x PCIe x16 (16 L), 3x PCIe x16 (4 L), 2x PCIe x16 (1 L); 2x PCIe x4 (4 L); RAID1, 2x 2 TB HDD (Enterprise) 3.5" SATA; Enclosure with drive support Type B (for internal installation/ 0.5 g vibration, 5 g shock); 2x 100/240V AC redundant industrial power supply unit; 64 GB DDR4 SDRAM (4x 16 GB), ECC, Dual Channel (only with Xeon); 512 GB SSD M.2 NVMe to PCIe x4 adapter card (1 slot occupied); (for operating system) and PCIe x16 graphics card (3x mDP: 3x adapter mDP to DP) (1 slot occupied); Windows Server 2016 Standard edition including clients, 64-bit, MUL (de, en, fr, it, es); Adapter cable DP acc. to DVI-D for onboard graphic; Without power supply cable
Product family	SIMATIC IPC847E
Product Lifecycle (PLM)	PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group	205 / 205
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None

Delivery information

Export Control Regulations	ECCN : 5A992 / AL : N
Estimated dispatch time (Working Days)	15 Day/Days
Net Weight (kg)	17,000 Kg
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	Not available
Commodity Code	84715000
LKZ_FDB/ CatalogID	IC10
Product Group	3354
Group Code	R133
Country of origin	Germany
Compliance with the substance restrictions according to RoHS directive	Since: 15.10.2018
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	1200	19-20-01-02
eClass	1400	19-20-01-02
eClass	600	19-20-01-02
eClass	710	19-20-01-02
eClass	800	19-20-01-02
eClass	900	19-20-01-02
eClass	910	19-20-01-02
ETIM	700	EC001413

ETIM	800	EC001413
ETIM	900	EC001413
IDEA	400	6606
UNSPSC	1500	43-21-15-06

;