



SIMATIC DP, ET 200eco PN, F-DI 8x24V /F-DQ 3x24V 2A , M12 PROFI-safe, up to PL E (ISO 13849), up to SIL 3 (IEC 61508), protection IP65/67

| General information                                      |                                                     |
|----------------------------------------------------------|-----------------------------------------------------|
| Firmware version                                         |                                                     |
| • FW update possible                                     | Yes                                                 |
| Vendor identification (VendorID)                         | 02AH                                                |
| Device identifier (DeviceID)                             | 0306H                                               |
| Product function                                         |                                                     |
| • I&M data                                               | Yes; I&M0 to I&M3                                   |
| Engineering with                                         |                                                     |
| • STEP 7 TIA Portal configurable/integrated from version | V15 with HSP 204                                    |
| Operating mode                                           |                                                     |
| • DI                                                     | Yes                                                 |
| • DQ                                                     | Yes                                                 |
| Supply voltage                                           |                                                     |
| Rated value (DC)                                         | 24 V                                                |
| Reverse polarity protection                              | Yes                                                 |
| power supply according to NEC Class 2 required           | Yes                                                 |
| Load voltage 1L+                                         |                                                     |
| • Rated value (DC)                                       | 24 V                                                |
| • permissible range, lower limit (DC)                    | 20.4 V                                              |
| • permissible range, upper limit (DC)                    | 28.8 V                                              |
| • Reverse polarity protection                            | Yes                                                 |
| Load voltage 2L+                                         |                                                     |
| • Rated value (DC)                                       | 24 V                                                |
| • permissible range, lower limit (DC)                    | 20.4 V                                              |
| • permissible range, upper limit (DC)                    | 28.8 V                                              |
| • Reverse polarity protection                            | Yes                                                 |
| Input current                                            |                                                     |
| Current consumption, typ.                                | 200 mA                                              |
| from supply voltage 1L+, max.                            | 4 A                                                 |
| from load voltage 2L+, max.                              | 4 A                                                 |
| Encoder supply                                           |                                                     |
| Number of outputs                                        | 2; Vs                                               |
| 24 V encoder supply                                      |                                                     |
| • Short-circuit protection                               | Yes; electronic (response threshold 1.4 A to 4.5 A) |
| • Output current, max.                                   | 800 mA; per output                                  |
| Power loss                                               |                                                     |
| Power loss, typ.                                         | 9 W                                                 |
| Address area                                             |                                                     |
| Address space per module                                 |                                                     |
| • Inputs                                                 | 8 byte                                              |

|                                                                 |                                      |
|-----------------------------------------------------------------|--------------------------------------|
| • Outputs                                                       | 6 byte                               |
| <b>Digital inputs</b>                                           |                                      |
| Number of digital inputs                                        | 8; 8 (one-channel); 4 (two-channel)  |
| Digital inputs, parameterizable                                 | Yes                                  |
| Input characteristic curve in accordance with IEC 61131, type 1 | Yes                                  |
| Number of simultaneously controllable inputs                    |                                      |
| all mounting positions                                          |                                      |
| — up to 60 °C, max.                                             | 8                                    |
| Input voltage                                                   |                                      |
| • Rated value (DC)                                              | 24 V                                 |
| • for signal "0"                                                | -30 V DC to +5 V DC                  |
| • for signal "1"                                                | 15 V DC to 30 V DC                   |
| Input delay (for rated value of input voltage)                  |                                      |
| for standard inputs                                             |                                      |
| — parameterizable                                               | Yes; 0.8 / 1.6 / 3.2 / 6.4 / 12.8 ms |
| Cable length                                                    |                                      |
| • unshielded, max.                                              | 30 m                                 |
| <b>Digital outputs</b>                                          |                                      |
| Number of digital outputs                                       | 3                                    |
| • in groups of                                                  | 3                                    |
| Short-circuit protection                                        | Yes; Electronic                      |
| • Response threshold, typ.                                      | 10 A                                 |
| Limitation of inductive shutdown voltage to                     | PM-switching: Typ. -26 V to (-48 V)  |
| Controlling a digital input                                     | No                                   |
| Switching capacity of the outputs                               |                                      |
| • on lamp load, max.                                            | 10 W                                 |
| Output current                                                  |                                      |
| • for signal "1" rated value                                    | 2 A                                  |
| • for signal "1" permissible range, max.                        | 2.4 A                                |
| • for signal "0" residual current, max.                         | 0.5 mA                               |
| Parallel switching of two outputs                               |                                      |
| • for uprating                                                  | No                                   |
| • for redundant control of a load                               | No                                   |
| Switching frequency                                             |                                      |
| • with resistive load, max.                                     | 30 Hz                                |
| • with inductive load, max.                                     | 0.1 Hz                               |
| • on lamp load, max.                                            | 10 Hz                                |
| Total current of the outputs (per group)                        |                                      |
| all mounting positions                                          |                                      |
| — up to 60 °C, max.                                             | 3.9 A                                |
| Cable length                                                    |                                      |
| • unshielded, max.                                              | 30 m                                 |
| <b>Encoder</b>                                                  |                                      |
| Connectable encoders                                            |                                      |
| • 2-wire sensor                                                 | No                                   |
| — permissible quiescent current (2-wire sensor), max.           | 0.5 mA                               |
| <b>Interfaces</b>                                               |                                      |
| Transmission procedure                                          | 100BASE-TX                           |
| Number of PROFINET interfaces                                   | 1                                    |
| <b>1. Interface</b>                                             |                                      |
| Interface types                                                 |                                      |
| • M12 port                                                      | Yes                                  |
| • integrated switch                                             | Yes                                  |
| <b>Interface types</b>                                          |                                      |
| M12 port                                                        |                                      |
| • Autonegotiation                                               | Yes                                  |
| • Autocrossing                                                  | Yes                                  |
| • Transmission rate, max.                                       | 100 Mbit/s                           |
| <b>Protocols</b>                                                |                                      |
| Supports protocol for PROFINET IO                               | Yes                                  |

|                                                                                                           |                                                    |
|-----------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| PROFINET CBA                                                                                              | No                                                 |
| PROFIsafe                                                                                                 | Yes                                                |
| PROFINET IO Device                                                                                        |                                                    |
| Services                                                                                                  |                                                    |
| — IRT with the option "high flexibility"                                                                  | No; module will participate within an IRT topology |
| — Prioritized startup                                                                                     | No                                                 |
| Open IE communication                                                                                     |                                                    |
| • TCP/IP                                                                                                  | No                                                 |
| • SNMP                                                                                                    | Yes                                                |
| • DCP                                                                                                     | Yes                                                |
| • LLDP                                                                                                    | Yes                                                |
| • ping                                                                                                    | Yes                                                |
| • ARP                                                                                                     | Yes                                                |
| Interrupts/diagnostics/status information                                                                 |                                                    |
| Diagnostics function                                                                                      | Yes                                                |
| Alarms                                                                                                    |                                                    |
| • Diagnostic alarm                                                                                        | Yes                                                |
| Diagnoses                                                                                                 |                                                    |
| • Diagnostic information readable                                                                         | Yes                                                |
| • Monitoring the supply voltage                                                                           | Yes; green "ON" LED                                |
| • Wire-break in actuator cable                                                                            | Yes                                                |
| • Wire-break in signal transmitter cable                                                                  | Yes                                                |
| • Short-circuit                                                                                           | Yes                                                |
| • Short-circuit encoder supply                                                                            | Yes                                                |
| • Group error                                                                                             | Yes; Red/yellow "SF/MT" LED                        |
| Potential separation                                                                                      |                                                    |
| between the load voltages                                                                                 | Yes                                                |
| between load voltage and all other switching components                                                   | No                                                 |
| between Ethernet and electronics                                                                          | Yes                                                |
| Potential separation channels                                                                             |                                                    |
| • between the channels                                                                                    | No                                                 |
| Isolation                                                                                                 |                                                    |
| tested with                                                                                               |                                                    |
| • 24 V DC circuits                                                                                        | 707 V DC (type test)                               |
| • Test voltage for interface, rms value [Vrms]                                                            | 1 500 V; According to IEEE 802.3                   |
| Degree and class of protection                                                                            |                                                    |
| IP degree of protection                                                                                   | IP65/67                                            |
| Standards, approvals, certificates                                                                        |                                                    |
| Suitable for safety-related tripping of standard modules                                                  | No                                                 |
| Highest safety class achievable in safety mode                                                            |                                                    |
| • Performance level according to ISO 13849-1                                                              | PLe                                                |
| • SIL acc. to IEC 61508                                                                                   | SIL 2 (single-channel), SIL 3 (two-channel)        |
| • SILCL according to IEC 62061                                                                            | SIL 3                                              |
| Probability of failure (for service life of 20 years and repair time of 100 hours)                        |                                                    |
| — Low demand mode: PFDavg in accordance with SIL2                                                         | < 6.00E-04, 1oo1 evaluation                        |
| — Low demand mode: PFDavg in accordance with SIL3                                                         | < 1.00E-05, 1oo2 evaluation                        |
| — High demand/continuous mode: PFH in accordance with SIL2                                                | < 1.00E-08 1/h, 1oo1 evaluation                    |
| — High demand/continuous mode: PFH in accordance with SIL3                                                | < 2.00E-10 1/h, 1oo2 evaluation                    |
| Probability of failure of the digital outputs (for service life of 20 years and repair time of 100 hours) |                                                    |
| — Low demand mode: PFDavg in accordance with SIL3                                                         | < 2.00E-05                                         |
| — High demand/continuous mode: PFH in accordance with SIL3                                                | < 7.00E-09 1/h                                     |
| Ambient conditions                                                                                        |                                                    |
| Ambient temperature during operation                                                                      |                                                    |
| • min.                                                                                                    | -25 °C                                             |
| • max.                                                                                                    | 60 °C                                              |
| connection method                                                                                         |                                                    |

|                                 |                                 |
|---------------------------------|---------------------------------|
| Design of electrical connection | 4/5-pin M12 circular connectors |
| Dimensions                      |                                 |
| Width                           | 60 mm                           |
| Height                          | 175 mm                          |
| Depth                           | 49 mm                           |
| Weights                         |                                 |
| Weight, approx.                 | 940 g                           |

last modified:

7/2/2024 