



Figure similar

*** spare part *** SIMATIC S7-200, digital output EM 222, only for S7-22X CPU, 4 DQ, 4-24 V DC; 5 A/channel source

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	3 W
Digital outputs	
Number of digital outputs	4
Short-circuit protection	No
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "1", min.	20 V DC
Output current	
• for signal "1" rated value	5 A
• for signal "1" permissible range for 0 to 55 °C, max.	5 A
• for signal "0" residual current, max.	30 µA
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	20 A
— Current per conductor/group, max.	5 A
horizontal installation	
— up to 55 °C, max.	20 A
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	5 A
— on lamp load, max.	50 W
— with resistive load, max.	5 A
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Potential separation	
Potential separation digital outputs	
• Potential separation digital outputs	Yes
• between the channels, in groups of	1
Isolation	
Isolation tested with	500 V AC

connection method	
Plug-in I/O terminals	Yes
Dimensions	
Width	45 mm
Height	80 mm
Depth	62 mm
Weights	
Weight, approx.	120 g

last modified:

5/22/2024 