



Figure similar

SIMATIC S7, Digital input SM 326, 8 DI; 24 V DC, NAMUR, fail-safe NAMUR input for SIMATIC S7 F-systems, up to Category 4 (EN 954-1)/ SIL3 (IEC61508)/PLE (ISO13849), 1x 40-pole

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	160 mA
from backplane bus 5 V DC, max.	90 mA
Encoder supply	
Number of outputs	8
Type of output voltage	8.2 V DC
Power loss	
Power loss, typ.	4.5 W
Digital inputs	
Number of digital inputs	8
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8
— up to 60 °C, max.	8
Input voltage	
• Type of input voltage	DC
Input current	
• for signal "0", max. (permissible quiescent current)	0.35 to 1.2 mA
• for signal "1", typ.	2.1 to 7 mA
Input delay (for rated value of input voltage)	
for NAMUR inputs	
— at "0" to "1", max.	1.2 to 3 ms
— at "1" to "0", max.	1.2 to 3 ms
Cable length	
• shielded, max.	200 m
• unshielded, max.	100 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostics indication LED	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
Ex(i) characteristics	
Module for Ex(i) protection	Yes
maximum values for connecting terminals for gas group IIC	
• U _o (no-load voltage), max.	10 V

• I_o (short-circuit current), max. • P_o (power output), max. • C_o (permissible external capacity), max. • L_o (permissible external inductivity), max. • U_m (voltage at non-intrinsically safe connecting terminals), max.	13.9 mA 33.1 mW 3 µF 80 mH 60 V DC/30 V AC
Potential separation	
Potential separation digital inputs	
• between the channels • between the channels and backplane bus • between the channels and the power supply of the electronics	Yes Yes Yes
Standards, approvals, certificates	
Highest safety class achievable in safety mode	
• acc. to EN 954 • Performance level according to ISO 13849-1 • SIL acc. to IEC 61508	Cat. 4 PL _e SIL 2 (single-channel), SIL 3 (two-channel)
Use in hazardous areas	
• ATEX certificate	99 ATEX 2671 X
Ambient conditions	
Ambient temperature during operation	
• max.	60 °C
connection method	
required front connector	1x 40-pin
Dimensions	
Width	80 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	482 g
last modified:	4/25/2024 