



***** Replacement part ***** SIMATIC S7-400H, CPU 414H Central processing unit for S7-400H and S7-400F/FH, 4 interfaces: 1 MPI/DP, 1 DP and 2 for sync modules, 1.4 MB memory (700 KB data/700 KB program)

General information	
Product type designation	CPU 414-4H
Supply voltage	
Rated value (DC)	Power supply via system power supply
Input current	
from backplane bus 5 V DC, typ.	1 800 A
from backplane bus 5 V DC, max.	2 A
Power loss	
Power loss, typ.	4.5 W
Memory	
Type of memory	RAM
Work memory	
• integrated (for program)	700 kbyte
• integrated (for data)	700 kbyte
• expandable	No
Load memory	
• expandable FEPRM	Yes; with Memory Card (FLASH)
• expandable FEPRM, max.	64 Mbyte
• integrated RAM, max.	256 kbyte
• expandable RAM	Yes; with Memory Card (RAM)
• expandable RAM, max.	64 Mbyte
Backup	
• present	Yes
• with battery	Yes; all data
• without battery	No
Battery	
Backup battery	
• Backup current, typ.	550 µA
• Backup current, max.	1 530 µA
• Feeding of external backup voltage to CPU	5 V DC to 15 V DC
CPU processing times	
for bit operations, typ.	0.06 µs
for word operations, typ.	0.06 µs
for fixed point arithmetic, typ.	0.06 µs
for floating point arithmetic, typ.	0.18 µs
CPU-blocks	
DB	
• Number, max.	4 095; DB 0 reserved
• Size, max.	64 kbyte
FB	

• Number, max.	2 048
• Size, max.	64 kbyte
FC	
• Number, max.	2 048
• Size, max.	64 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	64 kbyte
Nesting depth	
• per priority class	24
Counters, timers and their retentivity	
S7 counter	
• Number	2 048
Retentivity	
— adjustable	Yes
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
S7 times	
• Number	2 048
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
Data areas and their retentivity	
Flag	
• Size, max.	8 kbyte
• Retentivity available	Yes; From MB 0 to MB 8 191
• Retentivity preset	MB 0 to MB 15
Address area	
I/O address area	
• Inputs	8 kbyte
• Outputs	8 kbyte
Process image	
• Inputs, adjustable	8 kbyte
• Outputs, adjustable	8 kbyte
• Inputs, default	1 024 byte
• Outputs, default	1 024 byte
Subprocess images	
• Number of subprocess images, max.	8
Digital channels	
• Inputs	65 536
— of which central	65 536
• Outputs	65 536
— of which central	65 536
Analog channels	
• Inputs	4 096
— of which central	4 096
• Outputs	4 096
— of which central	4 096
Hardware configuration	
Number of expansion units, max.	21
Multicomputing	No
Interface modules	

• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	6; IM 463-2
Number of DP masters	
• integrated	2
• via CP	10
• via IM 467	0
• Mixed mode IM + CP permitted	No; IM 467 cannot be used jointly with CP 443-5 Ext.
• via interface module	0
Number of operable FMs and CPs (recommended)	
• FM	32; Limited by number of slots and number of connections
• CP, PtP	32; Limited by number of slots and number of connections
• CP, LAN	32; Limited by number of slots and number of connections
Slots	
• required slots	2
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
Operating hours counter	
• Number	8
Clock synchronization	
• supported	Yes
1. Interface	
Interface type	MPI/PROFIBUS DP
Isolated	Yes
Interface types	
• RS 485	Yes
Protocols	
• MPI	Yes; Default setting
• PROFIBUS DP master	Yes
• PROFIBUS DP device	No
MPI	
• Number of connections	32
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
PROFIBUS DP master	
• Number of connections, max.	32
• Transmission rate, max.	12 Mbit/s
• max. number of DP devices	32; Number of slots, max. 512
Services	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	No
— S7 communication, as client	No
— S7 communication, as server	No
— Equidistance	No
— SYNC/FREEZE	No
— activation/deactivation of DP devices	Yes
— Direct data exchange (slave-to-slave communication)	No
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte

1st interface / DP master / payload data per DP Device / header	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
2. Interface	
Interface type	PROFIBUS DP
Isolated	Yes
Interface types	
• RS 485	Yes
Protocols	
• PROFIBUS DP master	Yes; Default setting
• PROFIBUS DP device	No
• Point-to-point connection	No
PROFIBUS DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• max. number of DP devices	96
Services	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	No
— S7 communication, as client	No
— S7 communication, as server	No
— Equidistance	No
— SYNC/FREEZE	No
— activation/deactivation of DP devices	No
— Direct data exchange (slave-to-slave communication)	No
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
2nd interface / DP master / payload data per DP Device / header	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
Protocols	
SIMATIC communication	
• S7 routing	Yes
communication functions / header	
PG/OP communication	Yes
Global data communication	
• supported	No
S7 basic communication	
• supported	No
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
S5 compatible communication	
• supported	Yes; via CP and loadable FC
• User data per job, max.	8 kbyte
Standard communication (FMS)	
• supported	Yes; Via CP and loadable FB
• User data per job, max.	Dependent on CP
Number of connections	
• overall	32
• usable for PG communication	
— reserved for PG communication	1
— adjustable for PG communication, max.	0

• usable for OP communication — reserved for OP communication — adjustable for OP communication, max. • usable for S7 basic communication — reserved for S7 basic communication — adjustable for S7 basic communication, max. • usable for routing — reserved for routing — adjustable for routing, max.	1 0 0 0 0 0
S7 message functions	
Number of login stations for message functions, max.	8
Test commissioning functions	
Diagnostic buffer	
• present • Number of entries, max. — adjustable — preset	Yes 3 200 Yes 120
configuration / header	
Configuration software	
• STEP 7	Yes; V5.0 SP2
configuration / programming / header	
Programming language	
— LAD — FBD — STL — SCL — CFC — GRAPH — HiGraph®	Yes Yes Yes Yes Yes Yes Yes
Know-how protection	
• User program protection/password protection	Yes
Dimensions	
Width	50 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	1 070 g
last modified:	4/25/2024 