

6GK1500-0FC10



PROFIBUS FC RS 485 plug 180 PROFIBUS connector with FastConnect connection plug and axial cable outlet for Industry PC, SIMATIC OP, OLM, Transfer rate: 12 Mbit/s, terminating resistor with isolating function, plastic enclosure.	
List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6GK1500-0FC10
Product Description	PROFIBUS FC RS 485 plug 180 PROFIBUS connector with FastConnect connection plug and axial cable outlet for Industry PC, SIMATIC OP, OLM, Transfer rate: 12 Mbit/s, terminating resistor with isolating function, plastic enclosure.
Product family	RS485 bus connector
Product Lifecycle (PLM)	PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group	5K2 / 5K2
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : N
Estimated dispatch time (Working Days)	1 Day/Days
Net Weight (kg)	0,047 Kg
Packaging Dimension	16,00 x 34,50 x 62,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	4025515076230
UPC	662643424447
Commodity Code	85366990
LKZ_FDB/ CatalogID	IK
Product Group	2452
Group Code	R323
Country of origin	Germany
Compliance with the substance restrictions according to RoHS directive	Since: 01.07.2008
Product class	A: Standard product which is a stock item could be returned within the returns guidelines/period.
WEEE (2012/19/EU) Take-Back Obligation	No
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	3654bbf1-1593-44bf-94f8-d055d47773f0

Classifications

	Version	Classification
eClass	1200	27-44-01-13
eClass	1400	27-44-01-13
eClass	600	27-26-07-03
eClass	710	27-44-01-01
eClass	800	27-44-01-01
eClass	900	27-44-01-01
eClass	910	27-44-01-01
ETIM	700	EC002636
ETIM	800	EC002636
ETIM	900	EC002636
IDEA	400	4690
UNSPSC	1500	39-12-14-62