

Product datasheet

Specifications



rectified and filtered power supply - 1 or 2-phase - 400 V AC - 24 V - 4 A

ABL8FEQ24040

 To be discontinued on: Dec 31, 2025 AD

 To be end-of-service on: Dec 31, 2026 AD

 To be discontinued

Main

Range of product	Modicon Rectified
Product or component type	Power supply
Power supply type	Rectified and filtered
Rated power in W	96 W
Nominal input voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2
Output voltage	24 V DC
Power supply output current	4 A
Anti-harmonic filter	Low frequency harmonic currents
Product certifications	cULus KC UL 508 EAC

Complementary

Network frequency limits	47...63 Hz
Input voltage limits	360...440 V 207...253 V
Power Factor	0.689 at 230 V 0.867 at 400 V
Efficiency	75 %
Power dissipation in W	24 W
Output coupling	Series Parallel
Output protection type	Against overload and short-circuits, protection technology: internal fuse, 4 A, 5 x 20 mm, T curve Against overvoltage, protection technology: 2 J peak limiter
Hold-up time	14 ms
Status LED	1 LED (green) output voltage 1 LED (orange) input voltage
Residual ripple	<= 1200 mV
Connections - terminals	For input connection: screw type terminals, connection capacity: 5 x 2.5...5 x 4 mm² AWG 14...AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 2.5...1 x 4 mm² AWG 14...AWG 11 For output connection: screw type terminals, connection capacity: 4 x 2.5...4 x 4 mm² AWG 14...AWG 11
Depth	164.0 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	108 mm
width	87 mm
Net weight	2.98 kg
Compatibility code	ABL8F

Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	0...95 % without condensation or dripping water
Operating altitude	3000 m
Vibration resistance	0.05 mm (f= 47...57 Hz) conforming to IEC 60068-1 0.7 gn (f= 13.9...47 Hz) conforming to IEC 60068-1 1 gn (f= 57...150 Hz) conforming to IEC 60068-1 1 mm (f= 3...13.9 Hz) conforming to IEC 60068-1
Safety class	Class I conforming to VDE 0106-1
Dielectric strength	2000 V between input and ground 4600 V between input and output 500 V between output and ground
Other environmental characteristic	EMC conforming to IEC 62041 Safety conforming to EN/IEC 61558-2-6 Safety conforming to UL 508 Safety conforming to UL 60950-1 EMC conforming to IEC 61000-3-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.500 cm
Package 1 Width	18.500 cm
Package 1 Length	11.500 cm
Package 1 Weight	3.220 kg
Unit Type of Package 2	P06
Number of Units in Package 2	30
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	109.600 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
-------------------	---

SCIP Number	93c35204-c30d-4a1c-be25-b7657ea12b91
-------------	--------------------------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

PVC free	Yes
----------	-----

Use Again

Repack and remanufacture


Circularity Profile

[End of Life Information](#)

Take-back	No
-----------	----

Dimensions Drawings

Dimensions



Dimensions in mm


a	b	c	G	J	Ø
87	165	108	60	96	5.5

Dimensions in in.

a	b	c	G	J	Ø
3.42	6.50	4.25	2.36	3.78	0.22


Connections and Schema

Internal Wiring Diagram



Performance Curves

Load Limits Curve



- (1) Nominal line supply + 10%
- (2) Nominal line supply
- (3) Nominal line supply - 10%

Image of product / Alternate images

Alternative



