

Product datasheet

Specifications



voltage transformer - 230..400 V - 2 x 115 V - 400 VA

ABT7PDU040G

⚠ Discontinued on: 20 Dec 2024

⚠ To be end-of-service on: 20 Dec 2025

⚠ To be discontinued

Main

Range of product	Modicon Transformer Universal
Product or component type	Safety and isolation transformer
Rated power in VA	400 VA
Input voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2
Output voltage	115/230 V AC
Secondary winding	Double
Protective cover	Without
Ambient air temperature for operation	-20...60 °C

Complementary

Input voltage limits	207...253 V 360...440 V
Network frequency limits	47...63 Hz
Input voltage tolerance	+/- 15 V
Efficiency	90 %
Power dissipation in W	44.4 W
Voltage variation at nominal load	0,0375 at 230 V 0,039 at 400 V
Output sustained overvoltage	0,033 (no load, hot state)
Maximum voltage drop at rated load	4.17 %
No load losses	21.28 W
Short-circuit voltage	0,041
Output protection type	Against overload, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection
Connections - terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm² AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 4 mm² AWG 11 For output connection: screw type terminals, connection capacity: 6 x 4 mm² AWG 11
Marking	CE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Fixing mode	By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on vertical panel, operating position: vertical By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %
Output coupling	Parallel Grounding of secondary Series by internal jumper
Operating altitude	3000 m
Electrical insulation class	Class B
width	150.0 mm
Height	113.0 mm
Depth	145.0 mm
Net weight	7.30 kg

Environment

Product certifications	EAC UR DNV-GL
Standards	UL 506
IP degree of protection	IP20
Environmental characteristic	EMC conforming to IEC 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-4
Ambient air temperature for storage	-40...80 °C
Relative humidity	0...95 % during operation
Overvoltage category	Class I conforming to VDE 0106-1
Dielectric strength	3200 V between input and ground 3200 V between output and ground 5100 V between input and output

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.000 cm
Package 1 Width	20.000 cm
Package 1 Length	20.000 cm
Package 1 Weight	7.628 kg
Unit Type of Package 2	P06
Number of Units in Package 2	19
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	157.932 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	93c35204-c30d-4a1c-be25-b7657ea12b91
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration
PVC free	Yes


Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
---------------------	--

Dimensions Drawings

Dimensions



Dimensions in mm


a	b	c	G	J	Ø
150	145	113	122	90.6	7

Dimensions in in.


a	b	c	G	J	Ø
5.91	5.71	4.45	4.80	3.57	0.27

Connections and Schema

Internal Scheme



Primary Voltage Wiring



Secondary Voltage Wiring

