

Product data sheet

Specifications



Panel PC Universal - Flash Disk SSD - 12" - DC - 0 slot - fanless

HMIPUF6D0701

Discontinued on: Dec 2, 2020

End-of-service on: Jun 30, 2023

Discontinued - Service only

Main

Range of Product	Harmony iPC
Product or Component Type	PC panel
Processor name	Intel icore 3rd generation 827E cache 3 MB
Chipset type	Intel BD82HM76
Display size	12 inch
Display colour	16 million colours
Luminance	34.8 fc (375 cd/m²)
Video controller type	Intel HD Graphics 3000
Operating system	Windows 7 64 bits Ultimatemulti-language
Software package	Vijeo Designer run time demo
Bezel material	Aluminium alloy

Complementary

Terminal type	Touchscreen display
Data storage equipment	>= 60 GB Flash disk SSD MLC 2000000 h
Display Type	Active matrix colour TFT LCD with LED backlight
Display Resolution	1024 x 768 pixels XGA
Backlight lifespan	50000 hours 77 °F (25 °C)
View angle horizontal x vertical	80 x 80°
Touch panel	Analogue resistive
Memory type	2 GB, expandable to 16 GB RAM DDR3
type of cooling	Fanless
Integrated connection type	2 Ethernet port - RJ45 COM1 serial link - male SUB-D 9 - RS232C 115 kbit/s)bottom COM2 serial link - male SUB-D 9 - RS232C 115 kbit/s)bottom DVI video portbottom audio output - mini-jack USB 2.0 type A 480 Mbit/s)front panel 4 USB 3.0 type A 5 Gbit/s)bottom
Port Ethernet	10BASE-T/100BASE-T/1000BASE-T
[Us] rated supply voltage	24 V DC +/- 25 % power supply
Inrush current	7 A
Power consumption in W	130 W

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	Die cast aluminium
Display material	Polyethylene sheet
Fixing mode	Enclosure door by fixing kit fasteners included)
Type of Installation	Indoor
Control type	ON/OFF push-button equipment ON and OFF) Push-button reset)
Local signalling	buzzer for power LED (multi-colour) for accessing Flash disk SSD (DISK) LED (orange) for link status LED for RUN LED
Width	12.3 in (313 mm)
Height	9.4 in (239 mm)
Depth	2.4 in (60 mm)
Cut-out dimensions	301.5 (+ 1/- 0) x 227.5 (+ 1/- 0) x 1.6...9 mm
Net Weight	8.8 lb(US) (4 kg)
Main type	Universal

Environment

IP degree of protection	IP65 front panel: conforming to EN/IEC 60529
NEMA degree of protection	NEMA 4X front panel
Product certifications	CULus 508 CULus CSA 22-2 No 142 CULus HazLoc Class I Division 2 UL 1604 CULus HazLoc Class I Division 2 ANSI/ISA 12-12-01 CULus HazLoc Class I Division 2 CSA 22-2 No 213 GOST CE C-tick
Pollution degree	2 EN/IEC 61131-2
Electromagnetic compatibility	Immunity to electromagnetic emissions, class A EN 55022 Immunity to electromagnetic emissions, class A EN 55011 Immunity to high frequency interference EN/IEC 61131-2 Immunity to high frequency interference EN/IEC 61000-4-x
Ambient air temperature for operation	32...122 °F (0...50 °C) vertical installation UL 508 32...113 °F (0...45 °C) vertical installation when using Gigabit Ethernet with HDD storage device UL 508 32...122 °F (0...50 °C) vertical installation IEC 61132-2 32...113 °F (0...45 °C) vertical installation when using Gigabit Ethernet with HDD storage device IEC 61132-2
Ambient air temperature for storage	-4...140 °F (-20...60 °C) IEC 60068-2-2 test Bb -4...140 °F (-20...60 °C) IEC 60068-2-14 test Na
Relative Humidity	10...85 % non-condensing EN/IEC 60068-2-78 10...85 % non-condensing EN/IEC 60068-2-30
Operating altitude	6561.68 ft (2000 m) EN/IEC 61131-2
Vibration resistance	1.75 mm 2...9 Hz) continuous EN/IEC 60068-2-6 Fc 3.5 mm 2...9 Hz) intermittently EN/IEC 60068-2-6 Fc 0.5 gn 9...200 Hz) continuous EN/IEC 60068-2-6 Fc 1 gn 9...200 Hz) intermittently EN/IEC 60068-2-6 Fc 1 mm 3...13.2 Hz) continuous EN/IEC 60068-2-6 Fc 0.7 gn 13.2...100 Hz) continuous EN/IEC 60068-2-6 Fc
Shock resistance	15 gn 11 ms IEC 60068-2-27, Ea tests

Ordering and shipping details

Category	22575-MAGELIS MC3
Discount Schedule	MC3
GTIN	3595864172514
Returnability	No
Country of origin	AT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.83 in (27.5 cm)
Package 1 Width	13.58 in (34.5 cm)
Package 1 Length	17.52 in (44.5 cm)
Package 1 Weight	13.2 lb(US) (6.0 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you](#) >

Use Better



Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance
(Product out of EU RoHS legal scope)

China RoHS Regulation

[China RoHS declaration](#)

Use Again



Repack and remanufacture


WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.



Dimensions Drawings

Dimensions




Mounting and Clearance


Spacing Requirement

Top, Bottom and Rear Sides	Left and Right Sides
 1 Air out 2 Air in	

Mounting Orientation



Panel Cut Dimensions



1 Installation panel

A	B	C
301.5 +1/0 mm (11.87 +0.04/0 in.)	227.5 +1/0 mm (8.96 +0.04/0 in.)	1.6...9 mm (0.06...0.35 in.)