Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



External power supply module, Harmony iPC, AC / DC adapter for

HMIYPSPMAC1

- ! Discontinued on: Sept 30, 2023
- ! To be end-of-service on: Mar 31, 2026

! Discontinued - Service only

Main

Range of product	Harmony iPC	
Product or component type	External power supply module	
Accessory / separate part category	Adaptation accessory	

Complementary

Accessory / separate part destination	HMIBM modular box PC HMIDAD Harmony iPC
Input voltage	110240 V AC 4763 Hz
Output voltage	24 V DC
[In] rated current	6.25 A
Range compatibility	Harmony iPC
width	7.4 in (189 mm)
Height	3.5 in (89.5 mm)
Depth	1.8 in (45.5 mm)

Environment

Ambient air temperature for operation	32158 °F (070 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)
Relative humidity	095 % non-condensing
Product certifications	CE UL 60950 cULus CSA 60950

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.91 in (15.0 cm)
Package 1 Width	9.06 in (23.0 cm)
Package 1 Length	14.57 in (37.0 cm)
Package 1 Weight	3.503 lb(US) (1.589 kg)
Unit Type of Package 2	S04

Number of Units in Package 2	3
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	12.50 lb(US) (5.67 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	China RoHS declaration

Use Again

